

Application No.: 10/633,107

BEST AVAILABLE COPY

Docket No.: P-5315C1

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the applications:

Listing of Claims

1. (Original) A locking element for a single use syringe, comprising:
 - a base including a generally trough-shaped body having a longitudinal axis;
 - a first leg extending from said base substantially parallel to said longitudinal axis;
 - a second leg extending from said base substantially parallel to said longitudinal axis, said second leg being in opposing relation to said first leg;
 - a first barb extending from said first leg;
 - a second barb extending from said second leg;
 - said first leg including a first end portion extending generally towards said longitudinal axis;
 - said second leg including a second end portion extending generally towards said longitudinal axis, and
 - a spring element for urging said barbs in a selected direction, said spring element attached to said base.
2. (Original) A locking element as described in claim 1 wherein said base, legs and spring element are of integral construction and formed from a substantially flat, integral sheet of metal.
3. (Original) A locking element as described in claim 1 wherein each of said first and second legs include an inner edge and an outer edge, said first and second barbs extending, respectively, from said outer edges of said first and second legs.
4. (Original) A locking element as described in claim 3 wherein said spring element includes a third leg extending between said first and second legs and adjacent to said inner edges thereof.

Application No.: 10/633,107

Docket No.: P-5315C1

5. (Presently Amended) A locking element as described in claim 4 wherein said third leg is ~~pivotably~~ pivorally attached to said base.

6. (Original) A locking element as described in claim 5 wherein said third leg has a bend therein.

7. (Original) A single use syringe assembly comprising:

a barrel having an inside surface defining a chamber for retaining fluid, and open proximal end and a distal end having a passageway in communication with said chamber;

a plunger rod assembly including an elongate body portion having a proximal end, a distal end, and a stopper mounted to said elongate body portion proximate said distal end, said stopper being slidably positioned in substantially fluid tight engagement with said inside surface of said barrel, said elongate body portion extending outwardly from said open proximal end of said barrel; and

a generally trough-shaped locking element positioned within said barrel, said locking element defining a channel, said elongate body portion of said plunger rod assembly extending through said channel;

one or more barbs extending from said locking element, said one or more barbs engaging said inside surface of said barrel for substantially preventing said locking element from moving proximally with respect to said barrel but allowing movement of said locking element towards said distal end;

said locking element engaging said elongate body portion of said plunger rod assembly such that said locking element is movable towards said distal end of said barrel as said plunger rod assembly is advanced, and

a spring member attached to said locking element and urging said one or more barbs towards said inside surface of said barrel.

8. (Original) A single use syringe assembly as described in claim 7 wherein said locking element includes first and second edges, said one or more barbs extending from said edges, and said spring member being integral with said locking element.

Application No.: 10/633,107

Docket No.: P-5315C1

9. (Original) A single use syringe assembly as described in claim 8 wherein said elongate body portion of said plunger rod assembly includes first and second adjoining portions, said first portion being distal of said second portion and having a smaller diameter than said second portion, a first shoulder separating said first and second portions, and a stop surface at the distal end of said first portion, said locking element having a distal end engageable with said stop surface and a proximal end engageable with said first shoulder.

10. (Original) A single use syringe assembly as described in claim 9 wherein said locking element includes a base and first and second legs extending from said base, said first and second legs being in substantially opposing relation and having end portions engageable with said elongate body portion of said plunger rod, said spring member comprising a third leg extending from said base between said first and second legs.

11. (Original) A single use syringe assembly as described in claim 10 wherein said first and second legs include inner edges adjoining said third leg and outer edges, said outer edges of said first and second legs including one or more barbs.

12. (Presently Amended) A single use syringe assembly comprising:

a barrel having an inside surface defining a chamber for retaining fluid;

a plunger rod assembly including an elongate body portion having a proximal end, a distal end and a stopper mounted to said elongate body portion, said stopper being slidably positioned in substantially fluid tight engagement with said inside surface of said barrel, said elongate body portion extending outwardly from said barrel;

a locking element positioned within said barrel, said locking element including a base including first and second opposing walls and a third wall connecting said first and second walls, a first leg extending proximally from said first wall, a second leg extending proximally from said second wall, said first and second legs being in opposing relation, a first barb extending from said first leg and engaging said inside surface of said barrel, a second barb extending from said second leg and engaging said inside surface of said barrel, said first leg including a first end portion engageable with said elongate body portion of said plunger rod assembly, said second leg including a second end portion engageable with said elongate body portion of said plunger rod assembly, said first and second barbs being positioned to

Application No.: 10/633,107

Docket No.: P-5315C1

substantially prevent said locking element from moving proximally in said barrel, but ~~not~~ allowing said locking element to move distally within said barrel; and ~~the means for resiliently urging said first and second barbs towards said inside surface of said barrel.~~

means for resiliently urging said first and said second barbs towards said inside surface of said barrel.

13. (Canceled) A single use syringe as described in claim 12 including means for resiliently urging said first and second barbs towards said inside surface of said barrel.

14. (Presently Amended) A single use syringe as described in claim ~~13~~ 12 wherein said means for resiliently urging including a third leg extending proximally from said third wall of said base, each of said first and second legs includes a substantially flat body having an inner edge substantially adjacent to said third leg and an outer edge, said first and second barbs extending, respectively, from said outer edges of said first and second legs.

15. (Original) A single use syringe as described in claim 14. wherein said locking element has a generally trough-shaped configuration.

16. (Original) A single use syringe as described in claim 15 wherein said elongate body portion of said plunger rod assembly includes first and second adjoining portions, said first portion being distal of said second portion and having a smaller diameter than said second portion, a first shoulder separating said first and second portions, and a stop surface at the distal end of said first portion, said first and second inwardly extending end portion of said first and second legs being engageable with said first shoulder, said locking element being engageable with said stop surface.

17. (Original) A single use syringe as described in claim 16 wherein said elongate body portion of said plunger rod assembly includes a second shoulder proximal of said first shoulder, said end portions of said first and second legs being engageable with said second shoulder.

Application No.: 10/633,107

Docket No.: P-5315C1

18. (Original) A single use syringe as described in claim 17 wherein the distance between said first shoulder and said stop surface is substantially the same as the length of said locking element.

19. (Original) A single use syringe as described in claim 18 wherein said locking element is formed from a substantially flat, integral sheet of metal.

20. (Original) A single use syringe as described in claim 12 wherein said locking element is formed from a substantially flat, integral sheet of metal.

21. (Original) A single use syringe as described in claim 20 including a spring member extending proximally from said base and urging said barbs towards said inside surface of said barrel, wherein each of said first and second legs includes a substantially flat body having inner and outer edges, said first and second barbs extending, respectively, from said outer edges of said first and second legs, said inner edges of said first and second legs being adjacent to said spring member.

22. (Original) A single use syringe as described in claim 21 wherein said locking element has a generally trough-shaped configuration.

23. (Original) A single use syringe as described in claim 21 wherein said spring member includes a third leg extending proximally from said third wall of said base, said third leg including a bend therein.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.